



3307 6 Avenue N
Lethbridge, Alberta
T1H 5C1

phone: 403.328.3800
fax: 403.328.4800
email: info@ducanindustries.com

Stand-Up Roll-Away Cot with Foam Mattress

Standard Features:

Constructed Using 16Ga Heavy Duty 1" Round Tubing
6" Foam Mattress (Meets CAL-129 & 16 CFR-1633
Requirements, So-Flux Anti-Microbial/Anti-Fungal
Double-Sewn Cover)

* See Technical Data Sheet for So-Flux OX

4 Easy-Roll Casters

Black Crutch Tips

Powdercoated Frame

Product Dimensions:

As Shown:

39"W x 78"L x 22"H

Supports a 39 x 75 x 6 Mattress

Options:

Powdercoat Colours - (Minimum required)

Can be produced to suit a 39 x 80 x 6 Mattress



Standard Powdercoat Finish Options



Black
Sandtex



Charcoal
Grey



Americano
Brown



3307 6 Avenue N
Lethbridge, Alberta
T1H 5C1

phone: 403.328.3800
fax: 403.328.4800
email: info@ducanindustries.com

Soflux Mattress Ticking

Soflux mattress ticking is a 200-210 denier Oxford Nylon fabric with a polyurethane coating. The product is designed for applications where an anti-microbial, fluid-proof durable mattress ticking fabric is required. University Housing applications are ideal candidates for Soflux.

Property:	Test Method:	Test Results:
Weight		4.6 oz. Sq. yd min.
Antibacterial	AATCC Method 147-1988 Staphylococcus aureus	Contact Inhibition 99% +
Antifungal	AATCC Method 30-1988 Aspergillus niger	Contact Inhibition 99% +
EPA Registration:	Bacteriostat 10466-28	Fungistat 10466-23
Flame Resistance	NFPA 701 CAL 117 BS EN 1021-1:1994 BS EN 1021-2:1994	PASS PASS PASS PASS
Cigarette Ignition	FF4-72/16cfr, Part 1632 (B)	PASS
Moisture Vapor Transmission	ASTM E96/BW	100g/m ² /24hr
Hydrostatic Burst (PSI)	Federal Standard 191-5512	200 lbs.
Tear Strength	Federal Standard 191-5134	Warp, 4.0 lbs. Fill, 4.0 lbs.